

ES/20SC, ES/20CCH, ES/20PC
EB/20SC, EB/20CCH, ES/20PC

Standard Features

- 12kW high efficiency heating elements
- Available standard and bakery depths
- Double deck convection oven is 64" in height
- Patented "plug-in, plug-out" control panel - easy to service
- Stainless Steel front, sides and top
- Dependent doors with windows
- Coved, fastener-free, porcelain interior
- Rugged double door with stainless steel door seals
- Heavy duty door handle
- Soft Air, two speed, 1/2 hp, fan motor
- 11-position rack guides and 5 plated oven racks
- Electronic ignition with solid state temperature controls
- Forced cool down fan mode
- Oven "ready" light -cycles with burners
- Interior oven lights
- Stainless steel rear jacket

Available Controls

SC-Standard Controls

140°F to 500°F solid state thermostat and 60 minute mechanical cook timer.

CCH-Cycle / Cook & Hold Control

150°F to 500°F temperature controller with 140°F to 200°F "Hold" thermostat Dual digital display shows time and temperature. A fan cycle timer pulses the fan.



(shown with optional casters)

STANDARD CONSTRUCTION SPECIFICATIONS

Exterior Finish: Stainless steel front, top, sides and rear jacket.

Doors: Dependent doors with windows. Stainless steel construction, heavy-duty welded steel frame and 5/8" diameter full-length hinge pin.

Electrical System: Terminal connections are located below oven section and are accessible from the front of the oven. These sheath type electrical heating elements located at the rear of the oven function as a single heating unit with a combined rating of 12 kW per deck. Available voltages include 208, 240, 380, and 480 VAC single or three phase, 50/60 Hz. Ovens equipped with 480VAC single or three phase heating elements use 240V controls and motors and do not require separate electrical lead wires.

Rack and Rack Guides: Heavy-duty removable wire rack

guides spaced on 1-5/8" centers offer 11 different rack positions. 5 wire racks provided with each oven.

Blower Fan and Motor: 1/2hp, 2-speed motor, 1725/1140

Oven Heating: Oven heating is regulated by an adjustable solid state thermostat control. Blower fan circulates air within the cavity "scrubbing" heat to the oven interior for even heat distribution within the cavity. Manual reset high limit temperature control protects the oven from overheat condition.

Control Panel: Located of front, at right side of oven, away from heat zone. Removable panel opens downward for easy servicing.


Legs: 6" stainless steel legs standard.

Note: Oven cannot be operated without fan in operation.



Job _____
Item# _____

Models: ES/20SC EB/20SC ES/20CCH EB/20CCH ES/20PC EB/20PC



Dimensions -in (mm)

MODEL	DEPTH			OVEN INTERIOR			RACK CLEARANCE		SHIPPING CRATE				
	A	B	C	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	DEPTH	HEIGHT	VOLUME	WEIGHT
ES/25	39.75" (1010)	30" (763)	34.38" (873)	29" (737)	22.5" (572)	20" (508)	28.25" (718)	22" (559)	55" (1399)	45.5" (1157)	81.50" (2070)	118 cu. ft. (3.34 cu. m.)	1040 lbs (471.7 kg.)
EB/25	46.75" (1187)	36.38" (924)	40.75" (1035)	29" (737)	28" (711)	20" (508)	28.25" (718)	27.25" (692)	55" (1399)	45.5" (1157)	81.50" (2070)	118 cu. ft. (3.34 cu. m.)	1180 lbs (523.2 kg.)

UTILITY INFORMATION

Standard: 1/2 horsepover, 2 speed motor, 1725/1140 r. p. m. per deck.

ELECTRICAL DATA		AMPS PER LINE				
EACH OVEN	VOLTAGE	1 PHASE	3 PHASE			
			X	Y	Z	NEUT.
12 kW Heating Elements and Controls	208 VAC, 60Hz	58	34	34	31	0
	220/240 VAC, 50Hz	46	28	28	24	0
	240 VAC, 60Hz	50	30	30	26	0
	380/220 VAC, 50Hz	32	17	17	21	4
	415/240 VAC, 50Hz	50	15	15	19	4
	480 VAC, 60Hz	25	14	14	13	0

* All units shipped single phase. Single phase units are easily converted to three phase.

MISCELLANEOUS

- Clearances from combustibles: Top, bottom, right, left side -0".
- Recommended - install under vented hood.
- Check local codes for fire and sanitary regulations.

NOTICE:

Southbend has a policy of continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

OPTIONS AND ACCESSORIES

- Stainless Steel oven interior
- Swivel Caster - front with locks
- Down draft diverter for direct flue
- Stainless Steel exterior bottom
- Knocked down packaging
- 3/4" quick disconnect with flexible hose (specify length: 3ft, 4ft, or 5ft)
- 208/240V 50/60 cycle (for use on 1 or 3 phase)
- Export Crating
- 2" air insulation panel (stainless steel only)
- Bold-down flanged legs
- Extra oven racks

**INTENDED FOR COMMERCIAL USE ONLY.
NOT FOR HOUSEHOLD USE.**



1100 Old Honeycutt Road, Fuquay-Varina, NC 27526
(919) 762-1000 www.southbendnc.com